

POLI-MASK 288

Product Information

Self adhesive stencil tape on the basis of a dimensionally stable polypropylene film with outstanding solvent resistance.

Suitable for lettering and spray mask applications on all varnished, glass, plastic and metal surfaces. POLI-MASK 288 can be used on flexible materials like PVC awnings and banner material as well.

Especially to be emphasised are the following properties:

- The detachable adhesive has an excellent durability on solvent contained screen-printing and awning materials. Can be easily removed without any residues.
- The polypropylene film possesses an optimal flat surface. Even if there is any solvent influence, no surface changes like creases or blistering is guaranteed.
- Outstanding sharp outline edges, therefore colour undermining on the outline edges are completely excluded.
- Can be used on freshly varnished surfaces without leaving any residues. Ideal for multi-colour lettering.
- The stencil tape can be cut with neat, sharp and accurate outlines, it is easy to weed and it can be easily transmitted without any problems.

Technical Data

Carrier:	Polypropyler	ne film, blue, translucent
Adhesive:	Acrylic	
Liner:	Silicone paper, white (140g/m ²)	
Adhesion [N/cm]:	1,70	+/- 10 %
Thickness [mm]:	0,10	+/- 5 %

Standard Dimensions

1.220 mm x 50 m

1.000 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.

 ${f SIGNSEEN}$ Arkeneel 27, 3905NS Veenendaal, The Netherlands

www.**signseen**.nl