

METAMARK APPLICATION FLUID

Page: 1

Compilation date: 03/03/2020

Revision date: 08/09/2020

Revision No: 2

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Sent to: Public Server Addition.

Product name: METAMARK APPLICATION FLUID

Index number: 2020F

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Cleaning Agent/Cleaner.

1.3. Details of the supplier of the safety data sheet

Company name: Leading Solvents

Marston Business Park

Rudgate Tockwith York

YO26 7QF

Tel: 01423 358058 **Fax:** 01423 358923

Email: enquiries@leading-solvents.co.uk

1.4. Emergency telephone number

Emergency tel: 01423 358058 (Office Hours Only)

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Flam. Liq. 3: H226

Most important adverse effects: Flammable liquid and vapour.

2.2. Label elements

Label elements:

Hazard statements: H226: Flammable liquid and vapour.

Hazard pictograms: GHS02: Flame



Signal words: Warning

Precautionary statements: P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P280: Wear eye protection, face protection.

METAMARK APPLICATION FLUID

Page: 2

P303+P361+P353: IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water.

P370+P378: In case of fire: Use media other than water to extinguish.

P403+P235: Store in a well-ventilated place. Keep cool.

2.3. Other hazards

Other hazards: In use, may form flammable / explosive vapour-air mixture.

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

ETHANOL - REACH registered number(s): 01-2119475610-43

EINECS	CAS	PBT / WEL	CLP Classification	Percent
200-578-6	00-578-6 64-17-5 Substance with a Community		Flam. Liq. 2: H225	1-10%
		workplace exposure limit.		

Non-classified ingredients:

DEMINERALISED WATER

EINECS	CAS	PBT / WEL	CLP Classification	Percent
-	-	-	-	70-90%

SURFACTANT OTPG - REACH registered number(s): 01-2119491296-29

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin. Wash

immediately with plenty of soap and water.

Eye contact: Immediately flood the eye with plenty of water for at least 15 minutes, holding the eye

open. Remove any contact lenses and open eyes wide apart. Get medical attention if

any discomfort continues

Ingestion: Wash out mouth with water.

Inhalation: Not applicable under normal use.

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be irritation of the throat.

Inhalation: No specific health warnings noted.

Delayed / immediate effects: No data available.

METAMARK APPLICATION FLUID

Page: 3

4.3. Indication of any immediate medical attention and special treatment needed

Immediate / special treatment: Not applicable.

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Alcohol resistant foam. Water spray. Carbon dioxide. Dry chemical powder.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: Flammable. In combustion emits toxic fumes. Forms explosive air-vapour mixture.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact

with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Notify the police and fire

brigade immediately. Eliminate all sources of ignition. Turn leaking containers leak-side

up to prevent the escape of liquid.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for

disposal by an appropriate method. Do not use equipment in clean-up procedure which

may produce sparks.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Smoking is forbidden. Use non-sparking tools. Ensure there is sufficient ventilation of

the area. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed. Keep away from

sources of ignition. Prevent the build up of electrostatic charge in the immediate area.

Ensure lighting and electrical equipment are not a source of ignition.

Suitable packaging: Original container stored in a dry and cool place.

METAMARK APPLICATION FLUID

Page: 4

7.3. Specific end use(s)

Specific end use(s): No data available.

Section 8: Exposure controls/personal protection

8.1. Control parameters

Workplace exposure limits: No data available.

DNEL/PNEC Values

DNEL / PNEC No data available.

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area. Ensure lighting and electrical

equipment are not a source of ignition.

Respiratory protection: Required, if exposure limit is exceeded. Filter ABEK P2.

Hand protection: Use suitable protective gloves if risk of skin contact.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Orange

Odour: Citrus.

Evaporation rate: No data available.

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Soluble

Viscosity: No data available.

Boiling point/range°C: 95-100 **Melting point/range°C:** No data available.

Flammability limits %: lower: 3.3 upper: 19.0

Flash point°C: 49 Part.coeff. n-octanol/water: No data available.

Autoflammability°C: >365 Vapour pressure: No data available.

Relative density: 0.992 pH: Approx 7

VOC g/I: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

METAMARK APPLICATION FLUID

Page: 5

10.2. Chemical stability

Chemical stability: Stable under normal conditions. Stable at room temperature.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

Decomposition may occur on exposure to conditions or materials listed below.

10.4. Conditions to avoid

Conditions to avoid: Heat. Hot surfaces. Sources of ignition. Flames.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents. Strong acids.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

ETHANOL

IVN	RAT	LD50	1440	mg/kg
ORL	MUS	LD50	3450	mg/kg
ORL	RAT	LD50	7060	mg/kg

Toxicity values: No data available.

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.Ingestion: There may be irritation of the throat.Inhalation: No specific health warnings noted.

Delayed / immediate effects: No data available.

Section 12: Ecological information

12.1. Toxicity

Ecotoxicity values: No data available.

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No bioaccumulation potential.

METAMARK APPLICATION FLUID

Page: 6

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

12.6. Other adverse effects

Other adverse effects: Negligible ecotoxicity.

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal

company.

NB: The user's attention is drawn to the possible existence of regional or national

regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN1170

14.2. UN proper shipping name

Shipping name: ETHANOL (ETHYL ALCOHOL)

(ETHANOL)

14.3. Transport hazard class(es)

Transport class: 3

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: No Marine pollutant: No

14.6. Special precautions for user

Special precautions: No special precautions.

Tunnel code: D/E
Transport category: 3

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Specific regulations: Not applicable.

15.2. Chemical Safety Assessment

Chemical safety assessment: A chemical safety assessment has not been carried out for the substance or the mixture

by the supplier.

METAMARK APPLICATION FLUID

Page: 7

Section 16: Other information

Other information

Other information: according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation

(EU) 2015/830

* indicates text in the SDS which has changed since the last revision.

Phrases used in s.2 and s.3: H225: Highly flammable liquid and vapour.

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H318: Causes serious eye damage.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive

and shall be used only as a guide. This company shall not be held liable for any

damage resulting from handling or from contact with the above product.



Bestel direct op SignSeen.nl

info@signseen.nl +31 (0) 318 502 897 Arkeneel 27 3905 NS Veenendaal